



บริษัท เชลล์แห่งประเทศไทย จำกัด The Shell Company of Thailand Limited

10 ถนนสุนทรโกษา คลองเตย กรุงเทพฯ 10110

10 Soonthornkosa Rd. Klongtoey, Bangkok 10110

โทร / Tel +66 (0) 2249 0491 โทรสาร / Fax +66 (0) 2249 8393

[www.shell.co.th](http://www.shell.co.th) or [www.shell.com](http://www.shell.com)

### Product Specification

#### SHELL V Power Nitro + Gasohol 95

Properties	Unit	Method		Limit
Research Octane Number (RON)	-	ASTM D-2699	min	95.0
Lead	g/l.	ASTM D-5059	max	0.005
Distillation :		ASTM D-86		
10%	°C		max	70
50%	°C		-	70-110
90%	°C		max	170
End Point	°C		max	200
Residue	%v.		max	2.0
Reid Vapour Pressure	kPa	ASTM D-4953	max	62
Sulphur Content	%wt.	ASTM D-4294	max	0.005
Phosphorus	g/l.	ASTM D-3231	max	0.0013
Silver Strip Corrosion	-	ASTM D-4814	max	1
Oxidation Stability	min	ASTM D-525	min	360
Existent Gum	mg/100ml.	ASTM D-381	max	4
Benzene Content	%v.	ASTM D-5580	max	1.0
Colour	-	Visual	-	Orange
Olefins	%v.	ASTM D6839	max	18
Aromatic Content	%v.	ASTM D-5580	max	35.0
Water Content	%wt.	ASTM E 203	max	0.7
Denature Ethanol	%v.	ASTM D 4815	-	9-10

For: THE SHELL COMPANY OF THAILAND LIMITED

..... *Ween Bun* .....

Fuels Technical Manager

\*The Company reserves the right to change the information contained herein without notice.