



บริษัท เชลล์แห่งประเทศไทย จำกัด The Shell Company of Thailand Limited

10 ถนนสุนทรโกษา คลองเตย กรุงเทพฯ 10110

10 Soonthornkosa Rd. Klongtoey, Bangkok 10110

โทร / Tel +66 (0) 2249 0491 โทรสาร / Fax +66 (0) 2249 8393

[www.shell.co.th](http://www.shell.co.th) or [www.shell.com](http://www.shell.com)

### Product Specification Shell Fuel Save Gasohol 91

Properties	Unit	Method		Limit
Research Octane Number(RON)	-	ASTM D-2699	min	91.0
Lead	g/l.	ASTM D-5059	max	0.005
Distillation :		ASTM D-86		
10%	°C		max	70
50%	°C		-	70-110
90%	°C		max	170
End Point	°C		max	200
Silver corrosion	number	ASTM D-4814	max	1
Residue	%v.		max	2
Reid Vapour Pressure	kPa	ASTM D-4953	max	62
Sulphur Content	%wt.	ASTM D-4294	max	0.005
Phosphorus	g/l.	ASTM D-3231	max	0.0013
Copper Strip Corrosion (50°C,3hrs.)	-	ASTM D-130	max	1
Oxidation Stability	min	ASTM D-525	min	360
Existent Gum	mg/100ml.	ASTM D-381	max	4
Benzene Content	%v.	ASTM D-5580	max	1.0
Colour	-	Visual	-	Green
Denatured Ethanal	%v.	ASTM D-4815	min	9
			max	10
Aromatic Content	%v.	ASTM D-5580	max	35.0

For :THE SHELL COMPANY OF THAILAND LIMITED

*Weer Bunn*

.....  
Fuels Technical Manager

\*The Company reserves the right to change the information contained herein without notice.