



The Shell Company of Thailand Limited

10 Soonthornkosa Rd. Klongtoey, Bangkok 10110

Telephone : +66(0)22626 6000, Fax : +66(0)2262 6183

www.shell.co.th or www.shell.com

Technical Data Sheet

Product name : Shell Comercial Diesel

Material code : 400010570

Properties	Units	Test Method	Specification
Appearance	-	Visual	Bright & Clear
Colour	-	-	Purple
Density at 15 °C	g/mL	ASTM D1298 or ASTM D4052	0.81 - 0.87
Calculated Cetane Index	-	ASTM D976	50 min.
Viscosity, Kinematic at 40°C	cSt(mm ² /s)	ASTM D445	1.8 - 4.1
Pour Point	°C	ASTM D97 or ASTM D5950	10 max.
Sulphur Content	mg/kg	ASTM D2622	10 max.
Corrosion, Copper Strip 3 hr at 50°C	-	ASTM D130	1 max.
Oxidation Stability	g/m ³ hr	ASTM D2274 or EN 15751	25 max. 35 min.
Carbon Residue on 10% Distillation Residue, Micro Method	% wt	ASTM D4530	0.30 max.
Water Content	mg/kg	EN ISO 12937	200 max.
Total Contamination	mg/kg	EN 12662	24 max.
Ash	% mass	ASTM D482	0.01 max.
Flash Point, PMcc	°C	ASTM D93	60 min.
Distillation: 90 % Recovered	°C	ASTM D86	357 max.
Polycyclic Aromatic Hydrocarbon	% wt	ASTM IP391 or ASTM D2425	8 max.
Methyl Ester of Fatty Acid	% vol	EN 14078	6.6 - 10.0
Lubricity by HFRR	µm	CEC F-06-A-96	460 max.

Effective date : 1st January 2024

** Sulphur content is under a waiver period of Euro 5 standard by DOE B

(Sompop Srivannavit)

Fuel Technical Manager

The Company reserved the right to change the information contained herein without notice.