



The Shell Company of Thailand Limited

10 Soonthornkosa Rd. Klongtoey, Bangkok 10110

Telephone : +66(0)22626 6000, Fax : +66(0)2262 6183

www.shell.co.th or www.shell.com

Technical Data Sheet

Product name : Shell U95

Material code : 400004580

Properties	Units	Test Method	Specification
Appearance	-	Visual	Bright & Clear
Research Octane Number (RON)	-	ASTM D2699	95.0 min.
Motor Octane Number (MON)	-	ASTM D2700	84.0 min
Lead Content	g/l	ASTM D5059	0.005 max.
Sulphur Content	%wt.	ASTM D2622	0.001 max.
Phosphorus Content	g/l	ASTM D3231	0.0013 max
Distillation			
- Distillation 10% Evaporated	°C	ASTM D86	70 max.
- Distillation 50% Evaporated	°C	ASTM D86	70-110
- Distillation 90% Evaporated	°C	ASTM D86	170 max.
- Distillation FBP	°C	ASTM D86	200 max.
Residue	%vol.	ASTM D86	2.0 max
Vapor Pressure	kPa	ASTM 5191	62.0 max.
Silver Strip Corrosion	minute	ASTM D4814	1 max.
Oxidation Stability	min.	ASTM D525	360 min.
Existent Gum	mg/100 ml	ASTM D381	4 max.
Colour	-		
- Hue	-	Visual	Yellow
- Intensity	-	ASTM D1500	0.5-1.5
Aromatic Content	%vol.	ASTM D5580	35 max.
Benzene Content	%vol.	ASTM D5580	1.0 max.
Olefins	%vol.	ASTM D6839	18 max.
Water Content	%wt.	ASTM E203	0.7 max.
Oxygenated Compounds	%vol.	ASTM D4815	5.5-11.0
Detergent Additive	-		According to DOEB registration

Effective date : 1st January 2024

(Sompop Srivannavit)

Fuel Technical Manager

Company reserved the right to change the information contained herein without notice.